CNCGLASS
CNC Ucolin Interlayer Technology Co., Ltd.
SHENZHEN, GD, CHINA
Peter Lin · cnc@cncglass.com · WhatsApp / Mobile +86 15013829504
WeChat wecan365 · www.cncglass.com

EPE Encapsulant Film: Protecting Photovoltaic and Laminated Assemblies

The abbreviation needs to be used carefully

EPE is used in more than one industry, and that has caused a great deal of avoidable confusion. Expanded polyethylene foam is a cushioning material for packing. The EPE we are asked about as an interlayer company is different: a co-extruded encapsulant, typically built as EVA faces around a polyolefin elastomer core, in thicknesses of the same order as solar EVA—often in the few-tenths of a millimeter to about one millimeter range. That sheet is not a shipping wrap. It is the layer that seals and electrically isolates a photovoltaic stack, and in some constructions it is also used where a higher resistivity barrier is wanted next to the cells.



Figure 1. A laminated glass specimen illustrating the clarity expected of a well-bonded interlayer.

The reason this structure exists is straightforward. EVA bonds readily to glass and is familiar to laminators. POE, in the core, offers a stronger moisture and ionic barrier than a typical EVA alone. Putting the two together aims to keep the line practice close to EVA while improving the package against damp heat and potential-induced degradation.

What the film is actually protecting

In a module, the hazards are heat, humidity, mechanical strain, and electric field, not the bumps of a parcel network. A well-chosen EPE sheet fills the stack, maintains peel to the glass, and presents a more resistive path against PID than many standard EVA grades. It also keeps the optical path clear, which is as important as the barrier: a seal that yellows or clouds still costs power.

Thickness is a design choice, not a packing grade. Thicker sheets can help with cell topography and with electrical clearance; thinner sheets can be appropriate where the layout is already flat and the cycle is well controlled. Width and roll length follow the laminator and the module format. None of these decisions should be borrowed from foam-packaging practice.

Specifying the sheet without folklore

We ask buyers to review transmittance, shrinkage, gel content or equivalent cure, peel, water-vapor behavior, and volume resistivity against the module they actually build. Isolated headline numbers, especially when they wander in

from another EPE meaning, do not help a process engineer. A short lamination trial on the production machine, followed by damp-heat and PID-related checks, is the only qualification we consider complete.

Storage rules resemble those for EVA: keep the rolls dry and within the stated temperature band, and respect the open time after the bag is opened. A co-extruded sheet is still a hygroscopic system at the EVA faces. Treating it casually in the store room undoes the advantage of the POE core.

Where this film earns its place

EPE encapsulant is a practical answer when a factory wants better moisture and PID behavior without abandoning EVA-like bonding faces. It is also part of the conversation for glass-glass and higher-voltage designs. It is not a universal replacement for every EVA, and it is not a cushioning foam for cartons.

Used under its correct name and under a documented cycle, it is a precise tool. That is how we specify it, and how we recommend it be bought.

If a drawing says EPE, we first confirm that it means a co-extruded EVA–POE–EVA encapsulant, then we qualify the sheet as we would any other reliability-critical interlayer: on optics, cure, adhesion, and barrier behavior, measured in the real stack.

Contact Us

Brand: CNCGLASS

Company: CNC Ucolin Interlayer Technology Co., Ltd.
Address: SHENZHEN, GD, CHINA
Contact: Peter Lin
Email: cnc@cncglass.com
WhatsApp / Mobile: +86 15013829504
WeChat: wecan365
Website: www.cncglass.com

We can help you compare EPE with EVA and POE, set a lamination window, and avoid mixing packaging-foam language with encapsulant specifications.